

Reset Circuit with Fixed Delay

Description


The EM6353 is an ultra-low current reset circuit available in a large variety of configurations and very small packages for maximum flexibility in all end-applications up to 125°C and using power supplies between 1.5V and 5.5V.

This circuit monitors the supply voltage of any electronic system, and generates the appropriate reset signal after a fixed reset timeout period. The threshold defines the minimum allowed voltage which guarantees the good functionality of the system. When V_{DD} rises above V_{TH} , the output remains active for an additional delay time. This allows the system to stabilize before getting fully active.


The EM6353 features three output types: active-low push-pull, active-low open-drain and active-high push-pull.

Small SOT23-3L package as well as ultra-low supply current of 2.9µA make the EM6353 an ideal choice for portable and battery-operated devices.

Typical Application



Pin Configuration (top view)




Features

- ❑ 200ms reset timeout period (25ms on request)
- ❑ Ultra-low supply current of 2.9µA ($V_{DD}=3.3V$)
- ❑ Operating temperature range: -40°C to +125°C
- ❑ ±1.5% reset threshold accuracy
- ❑ 11 reset threshold voltages V_{TH} : 4.63V, 4.4V, 3.08V, 2.93V, 2.63V, 2.2V, 1.8V, 1.66V, 1.57V, 1.38V, 1.31V
- ❑ 3 reset output options:
 - Active-low \overline{RESET} push-pull
 - Active-low \overline{RESET} open-drain
 - Active-high RESET push-pull
- ❑ No external components
- ❑ Immune to short negative V_{DD} transients
- ❑ Guaranteed Reset valid down to 0.8V
- ❑ Threshold hysteresis: 2.1% of V_{TH}
- ❑ Very small SOT23-3L package

Applications

- ❑ Mobile phones
- ❑ Set-top boxes
- ❑ Video, digital cameras, DVD players and recorders
- ❑ Modems
- ❑ Personal computers
- ❑ Switching hubs
- ❑ Copiers and fax
- ❑ Utility meters

Block Diagram



Pin Description

Pin		Name	Function
SOT23-3L "beta"	SOT23-3L "alpha"		
1	3	GND	Ground
2	1	\overline{RESET}	Active-low \overline{RESET} output. \overline{RESET} remains low for the reset timeout period after all reset conditions are deasserted and then goes high.
		RESET	Active-high RESET output. RESET remains high for the reset timeout period after all reset conditions are deasserted and then goes low.
3	2	V_{DD}	Supply Voltage (5.5V max.)
-	-	N.C.	Not connected. Not internally connected.

Ordering Information

EM6353		B	X	2SP3B	-	2.9	+
Reset Output Type:				RoHS Compliance:			
B = 200ms				+ = lead-free/green mold compliant			
A = 25ms				[blank] = leaded			
Reset Output Type:				Reset Threshold Voltage (V_{TH}):			
X = Active-low /RES push-pull				1.3 = 1.31V		2.6 = 2.63V	
Y = Active-low /RES open-drain				1.4 = 1.38V		2.9 = 2.93V	
Z = Active-high RES push-pull				1.6 = 1.57V		3.1 = 3.08V	
Package:				1.7 = 1.66V		4.4 = 4.40V	
1SP3B = SOT23-3 "alpha", Tape&Reel 3k pcs				1.8 = 1.80V		4.6 = 4.63V	
2SP3B = SOT23-3 "beta", Tape&Reel 3k pcs				2.2 = 2.20V			

Note: Subject to availability (see standard versions list below). Please give complete Part Number when ordering. All parts are offered in tape-and-reel only (3000 units).

Standard Versions (Top Marking)

Part Number	Top Marking ¹⁾	Top Marking ²⁾ with 4 Characters
EM6353BX2SP3B-3.1+	C5##	BLWJ
EM6353BY2SP3B-3.1+	CH##	BLWV
EM6353BZ2SP3B-3.1+	CJ##	BLW7
EM6353BX1SP3B-4.4+	C2##	BLBK
EM6353BX2SP3B-4.4+	C8##	BLWK
EM6353BX1SP3B-2.6+	CK##	BLBG
EM6353BX2SP3B-2.6+	BW##	BLWG
EM6353BY2SP3B-2.6+	C9##	BLWT
EM6353BX1SP3B-4.6+	CL##	BLBL

Part Number	Top Marking ¹⁾	Top Marking ²⁾ with 4 Characters
EM6353BX2SP3B-4.6+	CE##	BLWL
EM6353BY2SP3B-4.6+	CF##	BLWX
EM6353BZ2SP3B-4.6+	CB##	BLW9
EM6353BX2SP3B-1.8+	CC##	BLWE
EM6353BX1SP3B-2.9+	C1##	BLBH
EM6353BX2SP3B-2.9+	BR##	BLWH
EM6353BY1SP3B-2.9+	BS##	BLBU
EM6353BY2SP3B-2.9+	C7##	BLWU
EM6353BZ2SP3B-2.9+	BV##	BLW6

¹⁾ Top marking is the standard from 2006. No bottom marking exists. Where ## refers to the lot number (EM internal reference only)

²⁾ Top marking with 4 characters is standard from 2003. For lead-free/green mold (RoHS) parts, the first letter of top marking with 4 characters begins with letter "B" instead of letter "A". Bottom marking indicates the lot number.

Standard Versions (Samples)

Part Number
EM6353BX2SP3B-3.1+
EM6353BY2SP3B-3.1+
EM6353BZ2SP3B-3.1+
EM6353BX1SP3B-4.4+
EM6353BX2SP3B-4.4+
EM6353BX1SP3B-2.6+
EM6353BX2SP3B-2.6+
EM6353BY2SP3B-2.6+
EM6353BX1SP3B-4.6+

Part Number
EM6353BX2SP3B-4.6+
EM6353BY2SP3B-4.6+
EM6353BZ2SP3B-4.6+
EM6353BX2SP3B-1.8+
EM6353BX1SP3B-2.9+
EM6353BX2SP3B-2.9+
EM6353BY1SP3B-2.9+
EM6353BY2SP3B-2.9+
EM6353BZ2SP3B-2.9+

Sample stock is generally held on **standard versions** only. Please contact factory for other versions not shown here and for availability of non standard versions.

Absolute Maximum Ratings

Parameter	Symbol	Conditions
Voltage at V_{DD} to GND	V_{DD}	-0.3V to +6V
Minimum voltage at any signal pin	V_{MIN}	GND - 0.3V
Maximum voltage at any signal pin	V_{MAX}	$V_{DD} + 0.3V$
Electrostatic discharge max. to MIL-STD-883C method 3015.7 with ref. to V_{SS}	V_{ESD}	2000V
Max. soldering conditions	T_{MAX}	250°C x 10s
Storage Temperature Range	T_{STG}	-65°C to +150°C

Stresses above these listed maximum ratings may cause permanent damage to the device. Exposure beyond specified operating conditions may affect device reliability or cause malfunction.

Handling Procedures

This device has built-in protection against high static voltages or electric fields; however, anti-static precautions must be taken as for any other CMOS component. Unless otherwise specified, proper operation can only occur when all terminal voltages are kept within the voltage range. Unused inputs must always be tied to a defined logic voltage level.

Operating Conditions

Parameter	Symbol	Min	Max	Unit
Supply voltage (note 1)	V_{DD}	0.8	5.5	V
Operating Temperature	T_A	-40	+125	°C

Electrical Characteristics

Unless otherwise specified: V_{DD} = 0.8V to 5.5V, T_A =-40°C to +125°C (note 1).

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Supply current (note 2)	I_{DD}	$V_{DD}=1.5V$	+25°C	-	4.6	μA
			-40°C to +125°C	-	7	
		$V_{DD}=3.3V$	+25°C	-	5.5	
			-40°C to +125°C	-	8.3	
		$V_{DD}=5.0V$	+25°C	-	6.3	
			-40°C to +125°C	-	9.6	
Threshold voltage (note 3)	V_{TH}	EM6353 – 1.3	+25°C	1.290	1.330	V
			-40°C to +85°C	1.245	1.382	
			-40°C to +125°C	1.221	1.387	
		EM6353 – 1.4	+25°C	1.359	1.401	
			-40°C to +85°C	1.311	1.456	
			-40°C to +125°C	1.286	1.461	
		EM6353 – 1.6	+25°C	1.546	1.594	
			-40°C to +85°C	1.492	1.656	
			-40°C to +125°C	1.463	1.663	
		EM6353 – 1.7	+25°C	1.635	1.685	
			-40°C to +85°C	1.577	1.751	
			-40°C to +125°C	1.547	1.758	
		EM6353 – 1.8	+25°C	1.773	1.827	
			-40°C to +85°C	1.710	1.899	
			-40°C to +125°C	1.678	1.906	
		EM6353 – 2.2	+25°C	2.167	2.233	
			-40°C to +85°C	2.090	2.321	
			-40°C to +125°C	2.050	2.330	
		EM6353 – 2.6	+25°C	2.591	2.669	
			-40°C to +85°C	2.499	2.775	
			-40°C to +125°C	2.451	2.785	
		EM6353 – 2.9	+25°C	2.886	2.974	
			-40°C to +85°C	2.784	3.091	
			-40°C to +125°C	2.731	3.103	
		EM6353 – 3.1	+25°C	3.034	3.126	
			-40°C to +85°C	2.926	3.249	
			-40°C to +125°C	2.871	3.262	
		EM6353 – 4.4	+25°C	4.334	4.466	
			-40°C to +85°C	4.180	4.642	
			-40°C to +125°C	4.101	4.660	
		EM6353 – 4.6	+25°C	4.561	4.699	
			-40°C to +85°C	4.399	4.885	
			-40°C to +125°C	4.315	4.903	
Threshold hysteresis	V_{HYS}	$T_A=+25^\circ C$	-	$2.1\% \bullet V_{TH}$	-	V

Note 1: Production tested at +25°C only. Over temperature limits are guaranteed by design, not production tested.

V_{DD} min=0.9V for active-high versions (EM6353_Z).

Note 3: Threshold voltage is specified for V_{DD} falling.

Electrical Characteristics (continued)


Unless otherwise specified: $V_{DD} = 0.8V$ to $5.5V$, $T_A = -40^{\circ}C$ to $+125^{\circ}C$ (note 1).

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reset timeout period	t_{POR}	V_{DD} from $0V$ to $V_{TH(typ)} + 15\%$ (note 2 and 4). $T_A = +25^{\circ}C$	EM6353B	155	200	224
			EM6353A	19.4	25	28
Propagation delay time V_{DD} to \overline{RESET} (\overline{RESET}) delay	t_P	V_{DD} drops from $V_{TH(typ)} + 0.2V$ to $V_{TH(typ)} - 0.2V$ (note 2). $T_A = +25^{\circ}C$	2	130	255	μs
Open-drain \overline{RESET} output Voltage	V_{OL}	$V_{DD} > 1V$	-	-	0.3	V
		$V_{DD} > 2.5V$	-	-	0.3	
		$V_{DD} > 5V$	-	-	0.3	
Push-pull \overline{RESET} / \overline{RESET} Output voltage	V_{OL}	$V_{DD} > 1V$	-	-	0.3	V
		$V_{DD} > 2.5V$	-	-	0.3	
		$V_{DD} > 5V$	-	-	0.35	
	V_{OH}	$V_{DD} > 1V$	0.8	-	-	
		$V_{DD} > 2.5V$	2	-	-	
		$V_{DD} > 5V$	4	-	-	
Output leakage current	I_{LEAK}	Only for EM6353_Y (open-drain)	-	-	0.5	μA

Note 1: Production tested at $+25^{\circ}C$ only. Over temperature limits are guaranteed by design, not production tested.
 V_{DD} min = $0.9V$ for active-high versions (EM6353_Z).

Note 2: \overline{RESET} (\overline{RESET}) open.

Note 4: Standard version is EM6353B ($t_{POR} = 200ms$), available at all times. EM6353A ($t_{POR} = 25ms$) is available by mask option and upon minimum order quantity. Please contact EM sales.


Timing Waveforms


Note 6: t_{SEN} = Maximum Transient Duration. Please refer to figure on next page.


Note 7: Overdrive = $V_{TH} - V_{DD}$. Please refer to figure on next page.

Typical Operating Characteristics


(Typical values are at $T_A = +25^\circ\text{C}$ unless otherwise noted, $\overline{\text{RESET}}$ or RESET open.)




I_{DD} vs. Temperature




Propagation Time t_P vs. Temperature



**Reset Timeout Period t_{POR} vs. Temperature
(normalized with respect to t_{POR} 25°C)**




**Maximum Transient Duration t_{SEN}
vs. Overdrive $V_{TH} - V_{DD}$**



Threshold Voltage Variation vs. Temperature (normalized)

Package Information



Traceability for small packages

Due to the limited space on the package surface, the bottom marking contains a limited number of characters that provide only partial information for lot traceability. Full information for complete traceability is however provided on the packing labels of the product at delivery from EM. It is highly recommended that the customer insures full lot traceability of EM product in his final product.

EM Microelectronic-Marín SA ("EM") makes no warranties for the use of EM products, other than those expressly contained in EM's applicable General Terms of Sale, located at <http://www.emmicroelectronic.com>. EM assumes no responsibility for any errors which may have crept into this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein.

No licenses to patents or other intellectual property rights of EM are granted in connection with the sale of EM products, neither expressly nor implicitly.

In respect of the intended use of EM products by customer, customer is solely responsible for observing existing patents and other intellectual property rights of third parties and for obtaining, as the case may be, the necessary licenses.

Important note: The use of EM products as components in medical devices and/or medical applications, including but not limited to, safety and life supporting systems, where malfunction of such EM products might result in damage to and/or injury or death of persons is expressly prohibited, as EM products are neither destined nor qualified for use as components in such medical devices and/or medical applications. The prohibited use of EM products in such medical devices and/or medical applications is exclusively at the risk of the customer

Product qualification is performed according to internal EM quality standards for industrial products. For any special requirement (eg. automotive grade) please contact EM Microelectronic-Marín S.A.